

LI-RHEX-01 Reducing Hex Nipple (Lintas)

Features

- Superior Quality Investment-casted Stainless Steel.
- Available in S.S 304(CF8) & S.S 316(CF8M) Grades.
- Precise machining
- Available in BSP / BSPT / NPT Threading as per requirement.
- Pressure Rating PN25, Test Pressure (Hyd.): -30 Kg./cm² (427 psig)
- Working Pressure 25 Kg./cm² (356 psig)

Suitability

Water, Air, Gas, Oil, Steam



Dimensions

Size	L (mm)	L (Inch)	S (mm)	S (Inch)
3/8"x1/8"	-	-	-	-
3/8"x1/4"	35.30	1.39	19.40	0.76
1/2"x1/4"	39.90	1.57	23.90	0.94
1/2"x3/8"	39.90	1.57	23.90	0.94
3/4"x1/4"	44.00	1.73	29.00	1.14
3/4"x3/8"	44.00	1.73	29.00	1.14
3/4"x1/2"	47.50	1.87	29.00	1.14
1"x3/8"	46.50	1.83	35.20	1.39
1"x1/2"	50.60	2.00	35.20	1.39
1"x3/4"	51.50	2.00	35.20	1.39
1.1/4"x1/2"	53.60	2.11	45.00	1.77
1.14"x3/4"	54.60	2.15	45.00	1.77
1.1/4"x1"	55.70	2.19	45.00	1.77
1.1/2"x1.1/4"	62.30	2.45	50.00	1.97
1.1/2"x1"	61.00	2.40	50.00	1.97
1.1/2"x3/4"	60.30	2.36	50.00	1.97
2"x1.1/2"	67.70	2.67	62.25	2.45
2"x1.1/4"	66.77	2.63	62.25	2.45
2"x1"	66.50	2.62	62.25	2.45

