

## LI-RSKT-01 Reducing Socket (Lintas)

### Features

- Superior Quality Investment-casted Stainless Steel.
- Available in S.S 304(CF8) & S.S 316(CF8M) Grades.
- Precise machining
- Available in BSP / BSPT / NPT Threading as per requirement.
- Pressure Rating PN25, Test Pressure(Hyd.): -30Kg./cm<sup>2</sup> (427 psig)
- Working Pressure 25 Kg./cm<sup>2</sup> (356 psig)

### Suitability

Water, Air, Gas, Oil, Steam



### Dimensions

Size	L (mm)	L (Inch)
3/8"x1/8"	31.00	1.22
1/2"x1/4"	31.00	1.22
1/2"x3/8"	31.00	1.22
3/4"x1/4"	-	-
3/4"x3/8"	34.00	1.34
3/4"x1/2"	37.70	1.48
1"x3/8"	-	-
1"x1/2"	40.30	1.49
1"x3/4"	40.90	1.61
1.1/4"x1/2"	50.50	1.99
1.14"x3/4"	50.50	1.99
1.1/4"x1"	50.50	1.99
1.1/2"x1.1/4"	58.00	2.28
1.1/2"x1"	57.00	2.24
1.1/2"x3/4"	50.60	1.99
2"x1.1/2"	60.50	2.38
2"x1.1/4"	60.50	2.38
2"x1"	60.50	2.38

