

LI-BV-01-SE Stainless Steel Two Piece Design Ball Valve Heavy Duty (Lintas)

Features

- Screwed female ends, available in BSPP, BSPT & NPT Threading standards
- Superior Quality Stainless steel Investment casting, full bore blow-off proof stem with Stainless Steel Ball, Teflon Seat & Seal,
- Handle lever operated.
- Available in SS304(CF8) & SS316(CF8M) Grades
- Design Standard: MSS SP - 110
- Pressure/Class Rating: 1000 WOG
- Testing Standard -API - 598/BS-6755 Part - 1

Suitability

Water, Air, Gas, Oil, Steam



Materials of Construction

Part Name	Specifications / Material	Qty
Body	SS:304 / SS:316	1
Connector	SS:304 / SS:316	1
Ball	SS:304 / SS:316	1
Stem	SS:304	1
Gland Nut	SS:304	1
Lever	SS:202	1
Seat / Seal	PTFE Teflon (Virgin)	5

Dimensions

Size (mm)	A	B	C ≈
08	1/4" BSP/NPT	54	50.00
10	3/8" BSP/NPT	54	50.00
15	1/2" BSP/NPT	61.00	56.50
20	3/4" BSP/NPT	74.00	64.00
25	1" BSP/NPT	85.00	71.50
32	1.1/4" BSP/NPT	95.00	73.50
40	1.1/2" BSP/NPT	110	88.00
50	2" BSP/NPT	125.00	94.50
65	2-1/2" BSP/NPT	140.00	122
80	3" BSP/NPT	171.00	130
100	4" BSP/NPT	196.00	158

